



# Explosion Proof Peristaltic Pump

**Model No.:** EXP600-A-IV-1/EasyPump

**Flow Rate:** 3.18-3100mL/min



## Product Features

- JDiven by explosion-proof motor, the power is strong.
- Stepless speed regulation, reversible inversion.
- IP rate: IP55, Explosion-proof grade:ExdIIBT4 Gb
- Suitable for inflammable and explosive industrial sites.



## Pump Head



YZ35(PPS)

Drive	Speed(rpm)	Pump Head	Tube Size	Flow Rate (mL/min)
EXP600-A-IV1/EasyPump	60-600	EasyPump	13#, 14#, 19#, 16#, 25#, 17#, 18#	3.18-2580
			15#, 24#, 35#, 36#	108-3100

## Technical Specifications

Speed range	Manual control: 180-600 rpm; Frequency converter control: 60-600rpm
Speed control	Manual stepless speed regulation/Inverter speed regulation
Voltage	3 phase 380V(standard)/3 phase 220V(optional)
Condition temperature	0-40°C
Relative humidity	<80%
Explosion-proof grade	ExdIIBT4 Gb, ExdIICT4
IP rate	IP55
Drive weight	30kg
Drive dimension(L xWxH)	424 x230x330(mm)



Dimension Drawing(Unit:mm)

